



**2800 litres (61.5 imp.gal.)
One Piece
2 Compartment Pump
Filter Combo Tank**

Details

Concrete Strength: 6500 psi (45 MPa) @ 28 Days
Air Entrainment: 5 - 7%
Reinforcement: 10 mm Rebar and Structural Fiber
Joint Seal: Butyl Rope Sealant Or Equivalent
Design For Earth Dead Load Only
Maximum Bury: 2.0 m (6.5')
Conforms To CSA B66-M2005

Options

Alternative Placement Of Inlet And Outlet Holes
Plastic Riser

Other Notes

Pump Draw Down - 81 litres (18 imp.gal) per Inch
Weight: 5800 lb (2630 kg)
Conforms To CSA B66M05
(Dalhousie University)

**ISLAND
CONCRETE PRODUCTS LTD.
SYDNEY SITE**

517 KELTIC DR.
Phone: 902-562-2426
PORT HASTINGS SITE
522 Hwy 105
Toll Free: 1-855-562-2426

**BROOKFIELD
CONCRETE PRODUCTS LTD.**

P. O. BOX 37, 778 HWY 2
BROOKFIELD, N. S.
B0N 1C0
Phone: 902-673-2225
Toll Free: 1-888-705-2225
Fax: 902-673-2255

DATE: March 2016
SCALE: 3/8" = 1'-0"
PROJECT:
LOCATION: Sheet # of

Brookfield Concrete Products Ltd.
Your Pre-cast Specialists

e-mail: info@brookfieldconcrete.ca

Island Concrete Products Ltd.
Sydney / Port Hastings

e-mail: info@islandconcreteproducts.ca