



2730 litres (600 imp.gal.) Two Piece Septic Tank

Details

Concrete Strength: 6500 psi (45 MPa) @ 28 Days
Air Entrainment: 5 - 7%
Reinforcement: 10 mm Rebar and Structural Fiber
Joint Seal: Butyl Rope Sealant Or Equivalent
Design For Earth Dead Load Only
Maximum Burry: 2.0 m (6.5')
Conforms To CSA B66-M2005

Options

24" Diameter Poured In Place Plastic
Riser And Cover On Inlet End
Alternative Placement Of Inlet And Outlet Holes

Other Notes

100 mm (4") Pipe Baffles Supplied
Weight: 7200 lb (2690 kg)
Conforms To CSA B66M05
(Dalhousie University)

ISLAND
CONCRETE PRODUCTS LTD.
SYDNEY SITE

517 KELTIC DR.
Phone: 902-562-2426
PORT HASTINGS SITE
522 Hwy 105
Toll Free: 1-855-562-2426

BROOKFIELD
CONCRETE PRODUCTS LTD.
P. O. BOX 37, 778 Hwy 2

BROOKFIELD, N. S.
B0N 1C0
Phone: 902-673-2225
Toll Free: 1-888-705-2225
Fax: 902-673-2255

Brookfield Concrete Products Ltd.

Your Pre-cast Specialists

e-mail: info@brookfieldconcrete.ca

Island Concrete Products Ltd.

Sydney / Port Hastings

e-mail: info@islandconcreteproducts.ca

DATE: March 2016
SCALE: 3/8" = 1'-0"
PROJECT:

LOCATION:
Sheet # of