



**2840 litres (625 imp.gal.)
Standard Two Piece
Septic Tank**

Details

Concrete Strength: 6500 psi (45 MPa) @ 28 Days
 Air Entraining: 5 - 7%
 Reinforcement: 10 mm Rebar and Structural Fiber
 Joint Seal: Butyl Rope Sealant Or Equivalent
 Design For Earth Dead Load Only
 Maximum Bury: 2.0 m (6.5')
 Conforms To CSA B66-M2005

Options

24" Diameter Poured In Place Plastic
 Riser And Cover On Inlet End
 Alternative Placement Of Inlet And Outlet Holes
 Plastic or Concrete Risers
 Special Order Single Compartment

Other Notes

100 mm (4") Pipe Baffles Supplied
 Weight: 6600 lb (2012 kg)
 Conforms To CSA B66M05
 (Dalhousie University)

**ISLAND
 CONCRETE PRODUCTS LTD.
 SYDNEY SITE**

517 KELTIC DR.
 Phone: 902-562-2426
 PORT HASTINGS SITE
 522 Hwy 105
 Toll Free: 1-855-562-2426

**BROOKFIELD
 CONCRETE PRODUCTS LTD.**

P. O. BOX 37, 778 HWY 2
 BROOKFIELD, N. S.
 B0N 1C0
 Phone: 902-673-2225
 Toll Free: 1-888-705-2225
 Fax: 902-673-2255

Brookfield Concrete Products Ltd.

Your Pre-cast Specialists

Island Concrete Products Ltd.

Sydney / Port Hastings

DATE: March 2016
 SCALE: 3/8" = 1'-0"
 PROJECT:
 LOCATION:
 Sheet # of

e-mail: info@brookfieldconcrete.ca

e-mail: info@islandconcreteproducts.ca