

**20430 litres  
(4500 imp.gal.)  
Five Piece Septic Tank  
Side Section: Pg 2 of 3**

**Details**

Concrete Strength: 6500 psi (45 MPa) @ 28 Days  
Air Entraining: 5 - 7%  
Reinforcement: 10 mm Rebar, Structural Fiber,  
6x6x6 Gauge Wire Mesh  
Joint Seal: Butyl Rope Sealant Or Equivalent  
Design For Earth Dead Load Only  
Maximum Bury: 1.5m (5')  
Conforms To CSA B66-M2005

**Options**


Alternative Placement Of Inlet Holes  
Plastic Risers Are Available

**Other Notes**

100 mm (4") Pipe Baffles Supplied  
Weight: 29,950 lb (13,585 kg)  
Conforms To CSA B66M05  
(Dalhousie University)

**ISLAND  
CONCRETE PRODUCTS LTD.  
SYDNEY SITE**  
517 KELTIC DR.  
SYDNEY SITE  
Phone: 902-562-2426  
522 Hwy 105  
Toll Free: 1-855-562-2426

**BROOKFIELD  
CONCRETE PRODUCTS LTD.**  
P. O. BOX 37, 778 Hwy 2  
BROOKFIELD, N. S.  
B0N 1C0  
Phone: 902-673-2225  
Toll Free: 1-888-705-2225  
Fax: 902-673-2255



DATE: March 2016  
SCALE: 3/8" = 1'-0"

PROJECT:  
LOCATION:  
Sheet # of

**Brookfield Concrete Products Ltd.**

Your Pre-cast Specialists

e-mail: info@brookfieldconcrete.ca

**Island Concrete Products Ltd.**

Sydney / Port Hastings

e-mail: info@islandconcreteproducts.ca